

1x2 and 2x2 PM Fused Coupler



FEATURES

- Low Excess Loss and Insertion Loss
- High Power Handling
- High Stability and Reliability
- High Extinction Ratio
- Operating On Both Fast and Slow Axes

APPLICATION

- Power Monitoring
- Coherent Communication
- Fiber Laser and Amplifier
- Fiber Gyroscope
- Fiber Sensor
- Instrumentation

PERFORMANCE SPECIFICATIONS

Parameter	Specifications						
	780±15, 850±15nm		980±15, 1064±15nm		1310±15, 1550±15nm		
Grade	P	A	P	A	P	A	
Insertion Loss (Max)	Coupling ratio: 50/50%	3.6/3.6dB	3.8/3.8dB	3.6/3.6dB	3.8/3.8dB	3.6/3.6dB	3.8/3.8dB
	40/60%	5.2/3.1dB	5.4/3.3dB	5.2/3.1dB	5.4/3.3dB	5.2/3.1dB	5.4/3.3dB
	30/70%	5.8/2.0dB	6.1/2.1dB	5.8/2.0dB	6.1/2.1dB	5.8/2.0dB	6.1/2.1dB
	20/80%	8.0/1.5dB	8.2/1.7dB	8.0/1.5dB	8.2/1.7dB	8.0/1.5dB	8.2/1.7dB
	10/90%	11.6/1.2dB	11.8/1.4dB	11.6/1.20dB	11.8/1.4dB	11.6/1.20dB	11.8/1.4dB
	5/95%	14.8/0.80dB	15.0/1.0dB	14.8/0.80dB	15.0/1.0dB	14.8/0.80dB	15.0/1.0dB
	2/98%	18.4/0.40dB	18.9/0.50dB	18.4/0.40dB	18.9/0.50dB	18.4/0.40dB	18.9/0.50dB
	1/99%	22.0/0.35dB	22.5/0.40dB	22.0/0.35dB	22.5/0.40dB	22.0/0.35dB	22.5/0.40dB
Excess loss (Max)	0.80dB	1.0dB	0.80dB	1.0dB	0.40dB	0.60dB	
ER* (High Ratio Port)	20dB	18dB	20dB	18dB	20dB	18dB	
ER* (Low Ratio Port)	16dB	14dB	16dB	14dB	16dB	14dB	
CR Tolerance @ λc	50/50 : ±3.0%; 40/60 : ±2.5%; 30/70 : ±2.0%; 20/80 : ±2.0%; 10/90 : ±1.0%; 5/95 : ±0.50%; 2/98 : ±0.30%; 1/99 : ±0.20%						
Thermal stability	≤ 0.005dB/°C						
Return loss	≥ 55dB						
Directivity	≥ 50dB						
Optical power (CW)	≤ 500mW						
Operating Temperature	- 20 to +75°C (- 40 to +85°C Available upon request)						
Storage Temperature	- 40 to +85°C						
Package Dimensions	A= Standard, Φ3.0xL54 for 250um; Φ3.0xL70 for 900um (all wavelengths) M=Compact, Φ3.0xL35 for 250um; Φ3.0xL54 for 900um (1550nm only)						

Note:

*ER: Extinction ratio.

IL is 0.3dB higher, RL 5dB lower and ER 2dB lower for each connector added.

Connector key is aligned to slow axis.

All values referenced are without connector.


1x2 and 2x2 PM Fused Coupler

MECHANICAL DIMENSIONS

A Package



M Package



PORT CONFIGURATIONS



ORDERING INFORMATION

Type	Grade	Operating Wavelength	Coupling Ratio	Port	Package	Fiber Type	Pigtail Style	Fiber Length	In Connector	Out Connector
PMS=Standard	P=P grade	78=780nm	50=50:50	102=1x2	A=A package	J=PM780	1=Bare fiber	07=0.75m	0=None	0=None
	A=A grade	85=850nm	40=40:60	202=2x2	M=M package	K=PM850	2=900um	10=1.0m	1=FC/APC	1=FC/APC
		98=980nm	30=30:70			L=PM980	loose tube	·	2=FC/PC	2=FC/PC
		06=1064nm	20=20:80			M=PM1310		·	3=SC/APC	3=SC/APC
		31=1310nm	10=10:90			N=PM1550		·	4=SC/PC	4=SC/PC
		55=1550nm	05=5:95						5=ST	5=ST
		SS=Custom	02=2:98						6=LC/UPC	6=LC/UPC
	01=1:99						7=LC/APC	7=LC/APC		